



SEGGIOLINO RIBALTABILE ASPORTABILE CON SEDUTA IN DOGHE IN PPL (DA APPENDERE AL MANIGLIONE NON INCLUSO, MINIMO CM.50)

removable folding seat (to hang on the handrail)

| | cm | Kg |
|---------|---------|-----|
| X831/XX | 43,5x44 | 4,7 |



| | | | | | | | | |
|---------------------------|------------------------|--------------------------|---------------------------|--------------------------|-------------------------|------------------------|--------------------------|---------------------|
| bianco lucido RAL 9016 | blu lucido RAL 5002 | verde lucido RAL 6005 | giallo lucido RAL 1003 | rosso lucido RAL 3002 | nero lucido RAL 9005 | nero opaco RAL 9005 | bianco opaco RAL 9016 | altri colori RAL |
|---------------------------|------------------------|--------------------------|---------------------------|--------------------------|-------------------------|------------------------|--------------------------|---------------------|



testo di capitolato:

seggolino doccia asportabile, ribaltabile con frizione per bloccaggio in posizione verticale. seduta con doghe bianche in ppl, struttura realizzata in acciaio inox 304, rivestita con materiale antiusura epossipoliestere (colore bianco RAL9016: con proprietà antibatteriche dei sali d'argento bio-goman). completo di: vite svasata di unione Ø10 mm, piattelli per fissaggio a parete in acciaio inox, a 6 fori, rosoni acciaio inox funzione "antivandalo" Ø75 mm. capacità di carico 150 kg. dimensioni mm 435(l) x 440(p) 470(h). tipo Goman codice X831/XX.

specifications:

shower seat removable and folding with clutch for locking in position. seat in white ppl slats, structure made of stainless steel 304, coated with anti-wear epoxy polyester material (color white RAL9016: with antibacterial properties of silver salts bio-goman). complete with: union screw countersunk Ø10 mm, fixing plates for wall in stainless steel, with 6 holes, rosettes in stainless steel with "anti-vandal" function Ø75 mm. load capacity 150 kg. dimensions mm 435 (w) x 440 (p) 470 (h). type Goman code X831/XX.

